



PROGEF Standard Flange adaptor PP-H ANSI SDR17.6/PN6 Combined jointing face: flat and serrated

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR- Infrared welding compatible
- Suitable for flange connections to metric (from d110 also to ANSI/ASME B16.5)
- Suitable for flange connections to metric
- Injection moulded

Flange adapters are designed to work with most butterfly valves
For bigger dimensions, see flange adaptors in other chapters

d	DN	SDR	PN	FM	Type	Code	Weight
(mm)	(mm)		(bar)				(kg)
50	40	17.6	6	IR	A	727 798 610	0.077
90	80	17.6	6	IR	A	727 798 613	0.273

d	d1	d2	d4	L	L1	L2	e
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
50	60	82	44	62	32	12	3.0
90	105	133	94	80	42	18	6.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>