



JRG LegioStop Schrägsitzventil Ventil mit Verschraubungen Optipress / Sanpress Rotguss

- Beschreibung: Totraum- und wartungsfreies Oberteil, nichtsteigendes Handrad mit optischer Stellungsanzeige, Ventilsitz und Ventilstange aus Chromnickelstahl
- Temperatur: max. 90°C
- Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
- Anschluss: Optipress / Sanpress

d (mm)	DN (mm)	JRG NPK Code	GF NPK Code	SP	Gewicht (kg)
15	12	5234.015	350 895 670	1	0.500
18	15	5234.018	350 895 671	1	0.490
22	20	5234.022	350 895 672	1	0.740
28	25	5234.028	350 895 673	1	1.180
35	32	5234.035	350 895 674	1	1.550
42	40	5234.042	350 895 675	1	2.250
54	50	5234.054	350 895 676	1	3.420

d (mm)	DN (mm)	d1 G (inch)	d2 G (inch)	d3 Rp (inch)	d4 (mm)	h (mm)	l1 (mm)	z1 (mm)	z2 (mm)	PN (bar)	⊙ (mm)
15	12	¾	½	¾	50	89	143	31	65	16	6
18	15	¾	½	¾	50	89	148	34	68	16	6
22	20	1	¾	¾	60	106	165	39	80	16	6
28	25	1 ¼	1	¾	70	127	182	42	93	16	6
35	32	1 ½	1 ¼	¾	80	149	205	47	107	16	6
42	40	1 ¾	1 ½	¾	90	170	246	48	118	16	6
54	50	2 ¾	2	¾	100	200	271	48	133	16	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>