



ABS Wafer-style intermediate installation butterfly valve type 145
With electric actuator 24V
With manual override
Flange standard metric/ANSI/BS/JIS

Model:




- Voltage 24V AC/DC
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Overall length according to EN 558, ISO 5752 (DN50-200 line 25, DN250-300 line 16)
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220

Option:

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit, Monitoring board, Position controller, Profibus DP board

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d	Size	DN	PN	kv-value	EPDM	Weight
(mm)	(inch)	(mm)	(bar)	(Δp=1 bar)	Code	(kg)
				(l/min)		
63	2	50	10	1470	199 145 522	4.161
75	2 ½	65	10	2200	199 145 523	4.257
90	3	80	10	3000	199 145 524	5.859
110	4	100	10	6500	199 145 525	6.395
140	5	125	10	11500	199 145 526	5.389
160	6	150	10	16600	199 145 527	9.910
225	8	200	10	39600	199 145 528	13.529

d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	Y	E	X8
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	461.4	190	356.7	90	133.3	75	78.8	45	104	40		189.3	122.3	297.5
75	474.3	190	363.8	90	139.9	75	85.1	46	115	54	35	189.3	122.3	297.5
90	486.1	190	365.9	90	145.6	60	91.2	49	131	67	50	189.3	122.3	297.5
110	521.4	190	378.0	90	166.4	60	105.7	56	161	88	74	189.3	122.3	297.5
140	548.1	190	391.0	90	180.0	60	118.8	64	187	113	97	189.3	122.3	297.5
160	569.2	190	405.0	90	189.0	60	130.9	72	215	139	123	189.3	122.3	297.5
225	628.1	190	431.0	90	210.5	60	158.3	73	267	178	169	189.3	122.3	297.5

d	Y2	M1	M2
(mm)	(mm)	(mm)	(mm)
63	60	107.3	82.7
75	60	107.3	82.7
90	60	107.3	82.7
110	60	107.3	82.7
140	60	107.3	82.7
160	60	107.3	82.7
225	60	107.3	82.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>