



## Adaptor union PVC-U/brass metric / BS Rp

### Model:

- Union Nut: PVC-U
- Union bush: Solvent cement socket metric
- Union End: Brass with parallel female thread Rp
- Gasket: O-ring EPDM code no. 748 410 006-014; d90 748 410 248

d (mm)	Thread Type	PN (bar)	Code	SP	Weight (kg)
20	Rp	16	721 550 506	10	0.088
25	Rp	16	721 550 507	10	0.145
32	Rp	16	721 550 508	5	0.175
40	Rp	16	721 550 509	2	0.322
50	Rp	16	721 550 510	2	0.467
63	Rp	16	721 550 511	8	0.776
* 75	Rp	10	721 550 512	2	1.360
90	Rp	10	721 550 513	2	2.003
		Rp	721 551 506	10	0.093
		Rp	721 551 507	5	0.145
		Rp	721 551 508	5	0.193
		Rp	721 551 509	2	0.344
		Rp	721 551 510	2	0.509
		Rp	721 551 511	2	0.776
		Rp	721 551 513	2	2.120

d (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	s (mm)	z1 (mm)	z2 (mm)	Thread size	Size	O-Ring EPDM
20	43	48	22	26	25	7	10	1	3.53 x 20.22	748410006
25	51	54	25	29	30	9	10	1 1/4	3.53 x 28.17	748410007
32	58	60	27	33	36	8	11	1 1/2	3.53 x 32.93	748410008
40	72	70	31	39	46	10	13	2	5.34 x 40.65	748410009
50	83	81	35	46	55	13	15	2 1/4	5.34 x 46.99	748410010
63	100	98	40	58	65	14	20	2 3/4	5.34 x 59.69	748410011
* 75	127	109	47	62	85	16	18	Tr 108x5	5.34 x 81.92	748410014
90	150	121	52	69	95	18	18	Tr 128x5	5.34 x 100.97	748410015
	43	48	22	26	25	7	9	1		
	51	54	25	29	30	9	8	1 1/4		
	58	60	27	33	36	8	9	1 1/2		
	72	70	31	39	46	10	11	2		
	83	75	35	41	55	13	11	2 1/4		
	100	88	40	48	65	14	12	2 3/4		
	150	121	52	69	95	18	19	Tr 128x5		

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>