


**Angle seat check valve type 304 PVC-U**  
**Transparent body with solvent cement spigots ASTM**

**Model:**

- For horizontal or vertical installation
- Leakproof even at minimum pressure
- Specific gravity of piston approx. 2 kg/dm<sup>3</sup>



DN (mm)	Size (inch)	PN (bar)	kv-value ( $\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
15	½	10	95	<b>192 304 006</b>	1	0.117	<b>192 304 031</b>	1	0.180
20	¾	10	180	<b>192 304 007</b>	1	0.179	<b>192 304 032</b>	1	0.250
25	1	10	327	<b>192 304 008</b>	1	0.297	<b>192 304 033</b>	1	0.385
32	1 ¼	10	484	<b>192 304 009</b>	1	0.580	<b>192 304 034</b>	1	0.460
40	1 ½	10	725	<b>192 304 010</b>	1	0.778	<b>192 304 035</b>	1	0.781
50	2	10	1130	<b>192 304 011</b>	1	1.297	<b>192 304 036</b>	1	1.475
80	3	10	2500	<b>192 304 013</b>	1	3.741	<b>192 304 038</b>	1	3.449

D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)
43	65	143	149	37
47	75	160	166	45
56	90	174	180	47
64	102	188	194	50
82	123	205	211	54
95	144	225	231	63
104	204	311	321	90

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
 info.ps@georgfischer.com Internet: <http://www.gfps.com>