



PROGEF Standard installation fitting type 314

Model:

- Material: PP-H
- Threaded outlet 1 1/4" NPSM
- For conventional hot gas back welding according to DVS 2207 part 3

Attention:

- pH sensors can also be used for dimensions above d180/DN150 and below d75/DN65 with 727 314 000 The length might have to be adjusted (sensor has to touch the medium)
- only for pressure less or low-pressure application
- pressure rate depends on quality of hot gas back welding
- please consult the instruction manual
- Installation by trained and certified welders only
- Sensor length depends on installation fitting

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

d (mm)	DN	PN* (bar)	Code	Weight (kg)	L (mm)	D (mm)	Sensor Type
65 - 150	65 - 150	-	727 314 000	0.050	68	38	flow X0, pH XX
200 - 350	200 - 350	-	727 314 001	0.057	102	38	flow X1
350 - 600	350 - 600	-	727 314 002	0.885	178	38	flow X2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>