


Ball valve type 374 PVC-U With threaded sockets Rp

Model:

- True double union safe block ball valve
- Ball seals PE/PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- z-dimension, valve end and union nut compatible with type 375

Range of use:

- Water application



Size (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)
3/8	10	16	70	161 374 521	60	0.125
1/2	15	16	185	161 374 522	60	0.130
3/4	20	16	350	161 374 523	40	0.205
1	25	16	700	161 374 524	30	0.295
1 1/4	32	16	1000	161 374 525	20	0.435
1 1/2	40	16	1600	161 374 526	12	0.690
2	50	16	3100	161 374 527	6	1.160
2 1/2	65	10	5000	161 374 528	3	2.200
3	80	10	7000	161 374 529	2	3.310
4	100	10	11000	161 374 530	1	5.925

Size (inch)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	z (mm)
3/8	50	55	76	67	42	40	48
1/2	50	55	80	67	42	40	48
3/4	59	61	91	77	48	45	53
1	68	69	102	87	54	51	58
1 1/4	80	81	116	102	62	59	68
1 1/2	94	91	126	119	72	70	78
2	115	113	149	146	86	84	93
2 1/2	145	129	184	179	110	103	118
3	168	146	212	209	128	120	140
4	210	179	244	250	150	141	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>