



Stress Less Pipe Support - Vertical Metric

- For use as a vertical pipe support. Includes elastomeric insert strips in support to provide friction and snug fit against pipe.
- Bracket provides strength for support during seismic or excessive loading events.
- For metric size pipe 20mm – 63mm.
- Includes steel hoop and plastic guide insert.
- Hoop is trivalent gold chromium-coated galvanized steel, compliant with ASTM B633.
- Guide insert is Polypropylene, Black, UV resistant.
- Mounts to any flat surface or standard strut support.
- Mounting holes in hoop for bolts size "SC" (not included).
- Fx, Fy and Fz are rated design loads, in lb-f (pounds-force) and N (Newtons), for respective x, y and z directions.

Size (mm)	Code
20	155 484 560
25	155 484 561
32	155 484 562
40	155 484 563
50	155 484 564
63	155 484 565

Size (mm)	H (mm)	CL (mm)	Hbp (mm)	H1 (mm)	L (mm)	L1 (mm)	W (mm)	W1 (mm)	M	Fyz	F-z
20	41	21	11	3	83	66	50	37	M6	150lbs / 660N	180lbs / 800N
25	47	25	12	3	88	71	50	37	M6	150lbs / 660N	180lbs / 800N
32	56	30	14	3	95	78	50	37	M6	150lbs / 660N	180lbs / 800N
40	58	28	8	3	102	86	50	37	M6	150lbs / 660N	180lbs / 800N
50	69	35	10	3	111	94	50	37	M6	150lbs / 660N	180lbs / 800N
63	89	49	17	3	124	107	50	37	M8	200lbs / 800N	240lbs / 880N

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>