



SYGEF Plus Lug-style, end installation butterfly valve type 065
PVDF-HP, with hand lever
Flange standard ANSI/ASME

Model:

- ANSI 150 Lug Connection
- PTFE liner
- PFA overmoulded stainless steel disk
- Tightness test according to EN 12266-1 leakage rate A or API 598

d	DN	Size	PN	Inch	Code	Weight
(mm)	(mm)	(inch)	(bar)	(inch)		(kg)
63	50	2	16	2	160 065 000	3.600
90	80	3	16	3	160 065 002	6.600
110	100	4	16	4	160 065 003	9.800
160	150	6	16	6	160 065 004	13.500

H	B	AV	Q	D	Y	X	E	L
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
262	68	138	56	162	26	9	43	210
312	92	164	56	216	66	17	46	210
352	107	179	66	254	86	24	52	340
414	134	214	66	315	140	47	56	340

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>