



Adaptor union PVC-U/brass metric / BS R

Model:

- Union Nut: PVC-U
- Union Bush: Solvent cement socket PVC-U metric
- Union End: Brass with taper male thread R
- Gasket: O-ring EPDM code no. 748 410 006-014; d90 748 410 248

d	Thread Type	Size	PN	Code	SP	Weight
(mm)		(inch)	(bar)			(kg)
20	R	½	16	721 550 906	10	0.125
25	R	½	16	721 550 957	5	0.196
25	R	¾	16	721 550 907	5	0.196
25	R	1	16	721 550 967	5	0.307
32	R	½	16	721 550 958	5	0.297
32	R	¾	16	721 550 968	5	0.297
32	R	1	16	721 550 908	5	0.283
40	R	1 ¼	16	721 550 909	2	0.502
50	R	1 ½	16	721 550 910	2	0.681
63	R	2	16	721 550 911	2	1.101
*	75	R 2 ½	10	721 550 912	2	1.706
90	R	3	10	721 550 913	1	2.662
	R	½		721 551 906	10	0.132
	R	¾		721 551 907	5	0.196
	R	1		721 551 908	5	0.282
	R	1 ¼		721 551 909	2	0.519
	R	1 ½		721 551 910	2	0.723
	R	2		721 551 911	2	1.091
	R	3		721 551 913	1	2.788

d	D	L	L1	L2	G	s	z
(mm)	(mm)	(mm)	(mm)	(mm)	(inch)	(mm)	(mm)
20	43	63	37	26	1	25	47
25	51	66	37	29	1 1/4	30	47
25	51	71	42	29	1 1/4	30	52
25	51	75	46	29	1 1/4	30	56
32	58	70	37	33	1 1/2	36	48
32	58	75	42	33	1 1/2	36	53
32	58	79	46	33	1 1/2	36	57
40	72	91	52	39	2	46	65
50	83	102	56	46	2 1/4	55	71
63	100	125	67	58	2 3/4	65	87
*	75	127	139	77	Tr 108x5	85	95
90	150	155	86	69	Tr 125x8	95	104
	43	63	37	26	1	25	46
	51	71	42	29	1 1/4	30	50
	58	79	46	33	1 1/2	36	55
	72	91	52	39	2	46	63
	83	97	56	41	2 1/4	55	67
	100	115	67	48	2 3/4	65	78
	150	155	86	69	Tr 128x5	95	104

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 5/5/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>