





PROGEF Standard Diaphragm valve type 514 With fusion sockets metric

Model:

- Material: PP-H
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)
20	15	½	10	125
25	20	¾	10	271
32	25	1	10	481
40	32	1 ¼	10	759
50	40	1 ½	10	1263
63	50	2	10	1728

d (mm)	NBR Code	EPDM Code	PTFE/ EPDM* Code	FKM Code	Weight (kg)
20	167 514 002	167 514 012	167 514 032	167 514 062	0.267
25	167 514 003	167 514 013	167 514 033	167 514 063	0.391
32	167 514 004	167 514 014	167 514 034	167 514 064	1.151
40	167 514 005	167 514 015	167 514 035	167 514 065	1.277
50	167 514 006	167 514 016	167 514 036	167 514 066	1.386
63	167 514 007	167 514 017	167 514 037	167 514 067	3.030

d (mm)	D (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)	closest inch (inch)
20	65	65	48	73	14	12	128	25	M6	96	7	½
25	80	65	58	81	18	12	150	25	M6	114	10	¾
32	88	87	65	107	22	12	162	25	M6	122	13	1
40	101	87	79	115	26	15	184	45	M8	140	15	1 ¼
50	117	135	91	148	32	15	210	45	M8	160	19	1 ½
63	144	135	111	166	39	15	248	45	M8	190	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>