



ecoFIT 3-dlg koppeling PE100 d20-110 mm / SDR11

uitvoering:

- voor conventioneel stomplassen conform DVS 2207
- IR = infrarood (IR Plus®) compatibel
- afdichting: O-ring EPDM of FKM
- materiaal ecoFIT wartel 3-delige koppeling: PP glasvezelversterkt

d (mm)	DN (mm)	PN (bar)	FM	EPDM Code	FKM Code	gewicht (kg)
75	65	10	IR	753 518 112	753 528 112	0,600
90	80	10	IR	753 518 113	753 528 113	0,637
110	100	10	IR	753 518 114	753 528 114	0,883

d (mm)	Do (mm)	Lmax (mm)	G (inch)	s1 (mm)	Z1 (mm)	Z2 (mm)	Bm1 (mm)	Bm2 (mm)
75	137,6	135	S110.1 x 5	4,5	69	66	26	34
90	137,6	134	S110.1 x 5	5,4	69	65	26	45
110	160,7	139	S129.7 x 5	6,7	74	65	34	45

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>