



PROGEF Plus outlet flange adaptor S5/SDR11
Combined jointing Face: flat and serrated

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- To wafer check valves Type 369
- Cleaned and double bagged

Attention:

- In conjunction with outlet flange adaptors, **flange rings for socket systems** must be used.

d	DN	SDR	PN	Code	Weight	L	L1	L2	D	D1	D2	r	e
(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	32	11	10	727 808 134	0.064	64	30	11	80	37	50	3	3.7
50	40	11	10	727 808 135	0.088	67	30	12	90	43	61	3	4.6
63	50	11	10	727 808 136	0.126	74	30	14	105	54	76	4	5.8
75	65	11	10	727 808 137	0.187	78	30	16	125	70	90	4	6.8
90	80	11	10	727 808 138	0.346	87	35	17	140	82	108	4	8.2
110	100	11	10	727 808 139	0.481	102	41	18	160	105	131	4	10.0
140	125	11	10	727 808 141	0.710	124	47	25	190	130	165	4	12.7
160	150	11	10	727 808 142	1.255	149	52	25	215	158	188	4	14.6
225	200	11	10	727 808 145	1.830	180	55	32	270	206	248	4	20.5
280	250	11	10	727 808 147	3.550	240	63	35	325	259	308	4	25.4
315	300	11	10	727 808 148	4.960	272	66	35	375	308	346	4	28.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>