






Butterfly valve type 567 PVC-C Hand lever with ratchet settings

Model:

- Overall length according to EN 558, ISO 5752
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d	Size	DN	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(inch)	(mm)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
				(l/min)						
63	2	50	10	740	163 567 002	1	1.257	163 567 022	1	1.268
75	2 ½	65	10	1500	163 567 003	1	1.366	163 567 023	1	1.174
90	3	80	10	2400	163 567 004	1	1.542	163 567 024	1	1.997
110	4	100	10	3800	163 567 005	1	2.231	163 567 025	1	2.715
140	5	125	10	8600	163 567 006	1	2.820	163 567 026	1	2.536
160	6	150	10	11400	163 567 007	1	3.881	163 567 027	1	3.904
225	8	200	10	19900	163 567 008	1	5.873	163 567 028	1	6.803
280	10	250	10	34000	163 567 009	1	14.328	163 567 029	1	12.998
315	12	300	10	50000	163 567 010	1	18.899	163 567 030	1	19.139

d	PTFE	Weight
(mm)	Code	(kg)
63	163 567 202	1.257
75	163 567 203	1.366
90	163 567 204	1.542
110	163 567 205	2.231
140	163 567 206	2.820
160	163 567 207	6.719
225	163 567 208	5.873
280		
315		

d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	Y	M1	M2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	278.9	115.2	269.0	90	133.3	23	78.8	45	104	40		66.8	64.7	205.5
75	291.8	115.2	271.8	90	139.9	23	85.1	46	115	54	35	66.8	64.7	205.5
90	303.6	115.2	273.9	90	145.6	23	91.2	49	131	67	50	66.8	64.7	205.5
110	342.2	115.2	336.0	90	166.4	23	105.7	56	161	88	74	70.1	64.9	255.5
140	368.9	115.2	349.0	90	180.0	23	118.8	64	187	113	97	70.1	64.9	255.5
160	390.0	115.2	363.0	90	189.0	23	130.9	72	215	139	123	70.1	64.9	255.5
225	455.1	149.4	543.0	90	210.5	23	158.3	73	267	178	169	86.3	103.6	409.5
280	555.0	149.4	574.0	125	262.6	23	206.1	113	329	210	207	86.3	103.6	409.5
315	599.4	149.4	599.7	125	284.3	23	228.8	113	379	256	253	86.3	103.6	409.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>