



JRGURED pressure reducing valve gunmetal

- Temperature: max. 30°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 400 kPa (4 bar)
- Secondary pressure: 200 - 600 kPa (2 - 6 bar)
- Connection: manometer
- Thread type d2 = G
- Thread type d3 = Rp
- *Discontinued with replacement

	DN (mm)	GN (inch)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
*	15	½	½	1303.015	350 712 301	1	0.620
*	20	¾	¾	1303.020	350 712 401	1	0.770
*	25	1	1	1303.025	350 712 501	1	1.340
*	32	1 ¼	1 ¼	1303.032	350 712 601	1	1.800
	40	1 ½	1 ½	1303.040	350 712 701	1	3.400
	50	2	2	1303.050	350 712 801	1	4.900
	65	2 ½	2 ½	1303.065	350 734 701	1	5.200

	DN (mm)	GN (inch)	d2 (inch)	d3 (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	PN (bar)	z (mm)	z (mm)
*	15	½	¾	¾	54	34	79	80	25	40	5
*	20	¾	1	¾	60	42	86	85	25	43	5
*	25	1	1 ¼	¾	72	52	110	100	25	50	6
*	32	1 ¼	1 ½	¾	80	64	121	120	25	60	6
	40	1 ½	1 ¾	¾	96	80	157	145	25	73	8
	50	2	2 ¾	¾	105	98	172	175	25	88	8
	65	2 ½	3	¾	105	98	172	180	25	90	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>