



Type 2551 Magmeter; Display Version no relays

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power source: 4 to 20mA: 21.6 to 26.4 VDC, 22.1mA max
- *Only Signet installation fittings
- Standard: FKM O-rings (EPDM or FFKM on request)

MFR #	Body	Communication Interface	Electrode	Sensor Type	Insertion Sensor Length	Pipe Size (inch)
3-2551-P0-42	PP	4-20mA	316L SS	Integral Mount	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0
3-2551-P1-42	PP	4-20mA	316L SS	Integral Mount	X1 (DN125 – DN200, 5" to 8")	5.0 - 8.0
3-2551-P2-42	PP	4-20mA	316L SS	Integral Mount	X2 (DN250 – DN900, 10" to 36")	10.0 - 36.0
3-2551-T0-42	PVDF	4-20mA	Titanium	Integral Mount	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0
3-2551-T1-42	PVDF	4-20mA	Titanium	Integral Mount	X1 (DN125 – DN200, 5" to 8")	5.0 - 8.0
3-2551-T2-42	PVDF	4-20mA	Titanium	Integral Mount	X2 (DN250 – DN900, 10" to 36")	10.0 - 36.0
3-2551-V0-42	PVDF	4-20mA	Hastelloy C	Integral Mount	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0
3-2551-V1-42	PVDF	4-20mA	Hastelloy C	Integral Mount	X1 (DN125 – DN200, 5" to 8")	5.0 - 8.0
3-2551-V2-42	PVDF	4-20mA	Hastelloy C	Integral Mount	X2 (DN250 – DN900, 10" to 36")	10.0 - 36.0

Code

159 001 279
159 001 280
159 001 441
159 001 442
159 001 443
159 001 461
159 001 281
159 001 282
159 001 463

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>