



Variable area flow meter type 350
Float in PVDF with magnet
With solvent cement sockets PVC-U metric

Model:

- Standard guiding rod PVDF with stainless steel core (V4A) for DN50 and DN65 see accessories for variable area flow meters
- Suitable limit switches see accessories for variable area flow meters

Scale range (l/h)	d (mm)	DN (mm)	Taper tube in PVC-U transp. O- Rings in EPDM Code	Weight (kg)	Taper tube in Polyamid O-rings in EPDM Code	Weight (kg)	Taper tube in Polysulfone O-rings in EPDM Code	Weight (kg)
50 - 500	32	25	199 350 100	0.440	199 350 120	0.440	199 350 140	0.440
100 - 1000	32	25	199 350 101	0.479	199 350 121	0.440	199 350 141	0.440
150 - 1500	40	32	199 350 102	0.643	199 350 122	0.575	199 350 142	0.615
250 - 2500	40	32	199 350 103	0.619	199 350 123	0.620	199 350 143	0.620
200 - 2000	50	40	199 350 104	0.900	199 350 124	0.900	199 350 144	0.900
300 - 3000	50	40	199 350 105	0.970	199 350 125	0.900	199 350 145	0.900
600 - 6000	50	40	199 350 106	0.925	199 350 126	0.900	199 350 146	0.900
600 - 6000	63	50	199 350 107	1.445	199 350 127	1.320	199 350 147	1.320
1000 - 10000	63	50	199 350 108	1.325	199 350 128	1.320	199 350 148	1.320
1500 - 15000	63	50	199 350 109	1.328	199 350 129	1.320	199 350 149	1.320
2000 - 20000	75	65	199 350 110	2.150	199 350 130	2.150	199 350 150	2.150
3000 - 30000	75	65	199 350 111	2.150	199 350 131	2.150	199 350 151	2.150
8000 - 60000	75	65	199 350 112	2.150	199 350 132	2.150	199 350 152	2.150

Scale range (l/h)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)
50 - 500	58	400	356	350	1 ½
100 - 1000	58	400	356	350	1 ½
150 - 1500	72	408	356	350	2
250 - 2500	72	408	356	350	2
200 - 2000	83	418	356	350	2 ¼
300 - 3000	83	418	356	350	2 ¼
600 - 6000	83	418	356	350	2 ¼
600 - 6000	101	432	356	350	2 ¾
1000 - 10000	101	432	356	350	2 ¾
1500 - 15000	101	432	356	350	2 ¾
2000 - 20000	135	444	356	350	3 ½
3000 - 30000	135	444	356	350	3 ½
8000 - 60000	135	444	356	350	3 ½

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>