


SYGEF ECTFE Type SDV Diaphragm Valve ISO With pneumatic actuator FC (fail safe to close)

Model:

- ISO/ DIN flange connection
- Material: PFA lined SSSt valve body, PTFE-T/FKM diaphragm
- With pneumatic actuator

Size (inch)	d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)
½	20	15	10	160 144 206	4.8
¾	25	20	10	160 144 207	5.3
1	32	25	10	160 144 208	6.4
1 ¼	40	32	10	160 144 209	7.8
1 ½	50	40	10	160 144 210	13.9
2	63	50	10	160 144 211	16.0
2 ½	75	65	10	160 144 212	19.8
3	90	80	8	160 144 213	32.8
4	110	100	7	160 144 214	46.7

L (mm)	D (mm)	D1 (inch)	D3 (mm)	D4 (mm)	D5 (mm)	H (mm)	H1 (mm)	H3 (mm)	H4 (mm)	H5 (mm)	H7 (mm)	Body
130	120	½	95	65	14	211	24	115	26	23	36	PFA lined SSSt
150	120	½	105	75	14	213	26	117	26	23	36	PFA lined SSSt
160	120	½	115	85	14	227	30	123	26	23	41	PFA lined SSSt
180	150	¾	140	100	18	253	35	141	36	36	52	PFA lined SSSt
200	180	¾	150	110	18	284	41	154	37	36	56	PFA lined SSSt
230	180	¾	165	125	18	302	44	159	37	36	70	PFA lined SSSt
290	280	¾	185	145	18	366	55	182	24	46	82	PFA lined SSSt
310	280	¾	200	160	18	373	60	200	24	46	100	PFA lined SSSt
350	335	¾	220	180	18	448	72	267	24	46	123	PFA lined SSSt

kv-value (m³/h)

7.8
10.0
15.0
22.5
37.0
65.0
95.0
134.0
200.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>