





Diaphragm valve type 514 PVC-U SF With solvent cement sockets ASTM

Model:

- Silicone free/paint-compatible
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches
- PN16 available as a configuration

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	PTFE/ EPDM* Code	SP	Weight (kg)
20	15	½	10	125	161 514 622	1	0.398	161 514 672	1	0.408
25	20	¾	10	271	161 514 623	1	0.529	161 514 673	1	0.540
32	25	1	10	481	161 514 624	1	1.165	161 514 674	1	1.185
40	32	1 ¼	10	759	161 514 625	1	1.427	161 514 675	1	1.447
50	40	1 ½	10	1263	161 514 626	1	2.542	161 514 676	1	2.572
63	50	2	10	1728	161 514 627	1	3.417	161 514 677	1	3.445

D (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)
65	65	43	73	14	12	136	25	M6	96	7
80	65	51	81	18	12	160	25	M6	114	10
88	87	58	107	22	12	176	25	M6	122	13
101	87	72	115	26	15	198	45	M8	140	15
117	135	83	148	32	15	232	45	M8	160	19
144	135	100	166	39	15	268	45	M8	190	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>