





**SYGEF Standard
Membranventil Typ 514
Mit Schweissmuffen metrisch**

Ausführung:

- Werkstoff: PVDF
- Doppelter Durchfluss im Vergleich zum Vorgängermodell
- Eine zentrale Gehäusemutter ersetzt vier Schrauben
- Verriegelbares Handrad
- Leicht ein- und ausbaubar
- Kurze Gesamtlänge

Option:

- Armatur individuell konfigurierbar
- Multifunktionsmodul mit selbstjustierenden Endschaltern

*Material O-Ring: FKM

d	DN	Zoll	PN	kv-Wert ($\Delta p=1$ bar)	PTFE/ EPDM*	NPK	Gewicht	PTFE/FKM*	NPK	Gewicht
(mm)	(mm)	(inch)	(bar)	(l/min)	Code		(kg)	Code		(kg)
20	15	½	10	125	185 514 032		0.358	185 514 052		0.349
25	20	¾	10	271	185 514 033		0.546	185 514 053		0.546
32	25	1	10	481	185 514 034		0.969	185 514 054		0.969
40	32	1 ¼	10	759	185 514 035		1.683	185 514 055		1.683
50	40	1 ½	10	1263	185 514 036		2.932	185 514 056		2.932
63	50	2	10	1728	185 514 037		2.995	185 514 057		2.995

d	D	D2	D3	H	H1	H2	L	L2	M	z	Hub = Hx	closest inch
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(inch)
20	65	65	43	73	14	12	128	25	M6	100	7	½
25	80	65	53	81	18	12	150	25	M6	118	10	¾
32	88	87	60	107	22	12	162	25	M6	126	13	1
40	101	87	74	115	26	15	184	45	M8	144	15	1 ¼
50	117	135	82	148	32	15	210	45	M8	164	19	1 ½
63	144	135	100	166	39	15	248	45	M8	194	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>