



Quick Connect Valve 700 (Pair) Swiveled end-connection: PVDF NPT 1"



The QC7 (Quick Connect 700) utilizing two full bore ball valves that only allow flow when both valves are open. The patented interlock design ensures that the valve cannot be disconnected while it is under pressure.

Model:

- Dual interlock lever mechanism
- 360° swiveled end-connections
- Color coding: Blue for supply // Red for return
- Fluid loss: Approx 5,5cc.
- Valve body: PVDF
- Sealing: EPDM

Description	DN (mm)	Size (inch)	Di (mm)	Do (mm)	DE (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Cv 100 (gal/min)	EPDM Code	SP	Weight (kg)
NPT - Blue	25	1	28	42	70	10	570	39	735 911 700	1	0.950
NPT - Red	25	1	28	42	70	10	570	39	735 911 702	1	0.950

Description	DN (mm)	L1 (mm)	L2 (mm)	M1-1 (mm)	M2-1 (mm)	Lmax (mm)	Hmax (mm)	Wopen	Wclosed
NPT - Blue	25	96	96	26.5	46	192	102	79.5	85.5
NPT - Red	25	96	96	26.5	46	192	102	79.5	85.5



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>