

**SYGEF 标准型**  
**PVDF#电动球阀 181型 100-230V**  
**带焊接承插端 公制**



**型号:**

- 防护等级：IP68
- 控制范围：90°
- 加热元件，位置反馈（开/关/中间位置）
- 内置不锈钢固定螺孔


**选项:**

- 提供其他阀门和执行机构配置
- 可选附件：失效返回单元，监测板，定位器，Profibus DP板，Modbus TCP板，Ethernet Interface卡

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ( $\Delta p=1$ bar) (l/min)	FKM code	weight (kg)
16	10	3/8	10	70	199 181 012	2,100
20	15	1/2	10	185	199 181 013	2,100
25	20	3/4	10	350	199 181 014	2,200
32	25	1	10	700	199 181 015	2,300
40	32	1 1/4	10	1000	199 181 016	2,600
50	40	1 1/2	10	1600	199 181 017	3,000
63	50	2	10	3100	199 181 018	3,800
75	65	2 1/2	10	5000	199 181 019	8,800
90	80	3	10	7000	199 181 020	10,710
110	100	4	10	11000	199 181 021	17,500



d (mm)	Actuator	B3 (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	z (mm)
16	EA25	25	50	122	M6	227	27	12	93	33	28	180	97	83	67
20	EA25	25	50	122	M6	227	27	12	95	33	28	180	97	83	66
25	EA25	25	58	122	M6	231	30	12	109	33	33	180	97	83	77
32	EA25	25	68	122	M6	237	36	12	119	33	36	180	97	83	83
40	EA25	45	84	122	M8	243	44	15	135	33	43	180	97	83	99
50	EA25	45	97	122	M8	249	51	15	147	33	45	180	97	83	105
63	EA25	45	124	122	M8	264	64	15	168	33	51	180	97	83	117
75	EA45	70	166	122	M8	313	85	15	233	33	68	180	98	82	167
90	EA45	70	200	122	M8	325	105	15	254	33	71	180	98	82	180
110	EA120	120	238	122	M12	363	123	22	301	33	82	180	98	82	215



# Data sheet

valid from: 2026/3/29



---

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>