



MSA 2.1 Automatic Electrofusion Unit with Bluetooth connectivity and protocols export

The MSA 2.1 automatic electrofusion unit combines lightweight and high efficiency, thanks to its inverter technology and furthermore provides fusion documentation in PDF. The unit is extremely fast and simple, with three basic operations required to operator: connect, scan, start the fusion. It is robust, safe and ergonomic.

All is meant to simplify the job: the barcode scanner, for long distance reading, the cooling system to joint in series, the icon system, to keep the interaction between user and machine intuitive. The entire welding process is controlled and regulated with energy output compensation depending on ambient temperature and the indication of cooling time.

The internal Bluetooth Low Energy device offers the possibility to monitor the fusion from remote and collect the data recorded via wireless with consumer smartphones, to send them to the headquarter even in real time.

The unit has 1000 protocols permanently stored in the internal memory. The user can copy the fusion reports in an USB stick to print them out in PDF format.

Scope of delivery includes: transport box, 1 pair of angle adapter clips 4.0 mm, 1 pair of angle adapter clips 4.7 mm, operating instructions and START/STOP badge. The mini Welding Book is available as option.

Technical Data:

- Operating temperature: -20°C to +50°C
- Main voltage and frequency: 230V (190V - 265V), 50-60Hz
- Fusion voltage: 8-42 V (48 V)
- Fusion data input mode: bar code, manual
- Fusion current: 90 A (max)
- Suggested power generators: 3.5 kVA
- USB Port: Type A
- Protection factor: Class 1 / IP 65
- Main cable: 4m / Fusion cable 4m
- Weight: ca. 26.2 lbs (11.9 kg)
- Display: Graphical LCD, adjustable contrast
- Independent from languages

Type	Code	weight (kg)
Barcode scanner, transport case, mini Welding Book	790 156 003	11.900
Barcode scanner, transport case, mini Welding Book, Swiss plug	790 156 006	11.900
Barcode scanner, transport case, mini Welding Book, 8m fusion cable	790 156 010	12.900

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>