



## ecoFIT reducer SDR11

### Model:

- Material: PE100
- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100
- Up to d 315 injection moulded, above machined

| d    | d1   | FM | Code        | PF           | Weight | L    | L1   | L2   | e    | e1   |
|------|------|----|-------------|--------------|--------|------|------|------|------|------|
| (mm) | (mm) |    |             |              | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) |
| 180  | 90   | IR | 753 908 877 | 2 68 240 011 | 0.678  | 157  | 45   | 22   | 16.4 | 8.2  |
| 180  | 110  | IR | 753 908 878 | 2 68 240 011 | 0.991  | 157  | 45   | 28   | 16.4 | 10.0 |
| 180  | 125  | IR | 753 908 879 | 2 68 240 011 | 0.528  | 136  | 45   | 32   | 16.4 | 11.4 |
| 180  | 140  | IR | 753 908 880 | 2 68 240 011 | 0.963  | 136  | 45   | 35   | 16.4 | 12.7 |
| 180  | 160  | IR | 753 908 881 | 2 68 240 011 | 1.094  | 136  | 45   | 40   | 16.4 | 14.6 |
| 200  | 180  | IR | 753 908 883 | 2 68 240 011 | 1.419  | 151  | 50   | 45   | 18.2 | 16.4 |
| 225  | 180  | IR | 753 908 885 | 2 68 240 011 | 1.999  | 171  | 55   | 45   | 20.5 | 16.4 |
| 250  | 160  |    | 753 908 890 | 2 68 240 011 | 2.416  | 194  | 60   | 40   | 22.7 | 14.6 |
| 250  | 225  |    | 753 908 887 | 2 68 240 011 | 2.766  | 182  | 60   | 55   | 22.7 | 20.5 |
| 280  | 225  |    | 753 908 892 | 2 68 240 011 | 1.943  | 105  | 30   | 20   | 25.4 | 20.5 |
| 280  | 250  |    | 753 908 891 | 2 68 240 011 | 1.802  | 70   | 30   | 18   | 25.4 | 22.7 |
| 315  | 225  |    | 753 908 897 | 2 68 240 011 | 3.491  | 130  | 30   | 30   | 28.6 | 20.5 |
| 315  | 250  |    | 753 908 896 | 2 68 240 011 | 2.379  | 100  | 30   | 20   | 28.6 | 22.7 |
| 315  | 280  |    | 753 908 895 | 2 68 240 011 | 1.684  | 63   | 30   | 18   | 28.6 | 25.4 |
| 355  | 225  |    | 753 900 011 | 2 68 240 040 | 4.700  | 245  | 90   | 55   | 32.3 | 20.5 |
| 355  | 250  |    | 753 900 012 | 2 68 240 040 | 4.400  | 245  | 90   | 60   | 32.3 | 22.7 |
| 355  | 280  |    | 753 900 013 | 2 68 240 040 | 4.100  | 245  | 90   | 70   | 32.3 | 25.4 |
| 355  | 315  |    | 753 900 014 | 2 68 240 040 | 3.700  | 245  | 90   | 80   | 32.3 | 28.6 |
| 400  | 225  |    | 753 900 015 | 2 68 240 040 | 7.963  | 260  | 95   | 60   | 36.4 | 20.5 |
| 400  | 280  |    | 753 900 017 | 2 68 240 040 | 6.200  | 260  | 95   | 70   | 36.4 | 25.4 |
| 400  | 315  |    | 753 900 018 | 2 68 240 040 | 10.829 | 260  | 95   | 80   | 36.4 | 28.6 |
| 400  | 355  |    | 753 900 019 | 2 68 240 040 | 4.800  | 260  | 95   | 90   | 36.4 | 32.3 |
| 450  | 280  |    | 753 900 020 | 2 68 240 040 | 9.000  | 230  | 60   | 70   | 40.9 | 25.4 |
| 450  | 315  |    | 753 900 021 | 2 68 240 040 | 8.000  | 230  | 60   | 80   | 40.9 | 28.6 |
| 450  | 355  |    | 753 900 022 | 2 68 240 040 | 7.400  | 230  | 60   | 90   | 40.9 | 32.3 |
| 450  | 400  |    | 753 900 023 | 2 68 240 040 | 6.600  | 230  | 60   | 95   | 40.9 | 36.4 |
| 500  | 400  |    | 753 900 026 | 2 68 240 040 | 10.000 | 230  | 60   | 95   | 45.5 | 36.4 |
| 500  | 355  |    | 753 900 025 | 2 68 240 040 | 10.800 | 230  | 60   | 90   | 45.5 | 32.3 |
| 500  | 450  |    | 753 900 027 | 2 68 240 040 | 8.300  | 200  | 60   | 60   | 45.5 | 40.9 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>