



JRG LegioStop Y-type valve Mapress gunmetal

- Description: free of water pockets and maintenance free top, non rising handwheel with optical position indicator, valve seat and valve stem made of stainless steel
- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Connection: Mapress
- Thread type d2 = G
- Thread type d3 = Rp

d	DN	JRG	GF	SP	Weight
(mm)	(mm)	Code	Code		(kg)
15	12	5228.015	350 895 684	1	0.480
18	15	5228.018	350 895 685	1	0.480
22	20	5228.022	350 895 686	1	0.670
28	25	5228.028	350 895 687	1	1.130
35	32	5228.035	350 895 688	1	1.600
42	40	5228.042	350 895 689	1	2.090
54	50	5228.054	350 895 690	1	3.250

d	DN	d1	d2	d3	d4	h	l1	l2	z1	z2	PN	⬡
(mm)	(mm)	(mm)	(inch)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(bar)	(mm)
15	12	15	½	¼	53	87	123	17	33	50	16	6
18	15	18	½	¼	53	87	125	16	33	51	16	6
22	20	22	¾	¼	53	105	133	27	35	56	16	6
28	25	28	1	¼	60	116	152	28	40	66	16	6
35	32	35	1 ¼	¼	70	130	178	25	47	80	16	6
42	40	42	1 ½	¼	90	148	196	29	48	89	16	6
54	50	54	2	¼	90	169	282	21	79	133	16	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>