



ChlorFIT Van Stone Flange (S) Schedule 80 CORZAN® CPVC

150 psi @ 73°F (10.3 bar @ 22.7°C)
HC = Honeycomb (Face)

Size (inch)	P/L	Code
½	625	9854-005
¾	625	9854-007
1	625	9854-010
1 ¼	625	9854-012
1 ½	625	9854-015
2	625	9854-020
2 ½	625	9854-025
3	625	9854-030
4	625	9854-040
6	625	9854-060
8	625	9854-080
10	B10	9854-100
12	B10	9854-120
14	A34	9854-140N
16	A34	9854-160N
18	A34	9854-180N
20	A34	9854-200N
24	A34	9854-240N

Size (inch)	Pack Qty	# holes	Bolt Dia. (inch)	bolt cir. dia. (inch)	D (inch)	L (inch)	N1 (inch)	R (inch)	ID (inch)	Design
½	5	4	½	2.38	3.50	1.03	0.11	0.57	0.63	HC
¾	5	4	½	2.75	3.88	1.15	0.13	0.58	0.84	HC
1	5	4	½	3.13	4.25	1.38	0.11	0.66	1.06	HC
1 ¼	5	4	½	3.50	4.63	1.45	0.14	0.69	1.40	HC
1 ½	5	4	½	3.88	5.00	1.59	0.15	0.76	1.61	HC
2	5	4	⅝	4.75	6.00	1.76	0.20	0.82	2.10	HC
2 ½	5	4	⅝	5.50	7.00	2.05	0.22	0.98	2.50	HC
3	5	4	⅝	6.00	7.50	2.25	0.30	1.02	3.11	HC
4	5	8	⅝	7.50	9.00	2.65	0.34	1.11	4.07	HC
6	2	8	¾	9.50	11.00	3.59	0.48	1.27	6.13	HC
8	2	8	¾	11.75	13.50	4.63	0.50	1.73	8.02	HC
10	2	12	⅞	14.25	16.00	5.63	0.50	1.73	10.09	HC
12	2	12	⅞	17.00	19.00	6.69	0.56	1.73	11.98	HC
14	1	12	⅞	18.75	21.00	11.75	0.50	4.75	12.50	FAB
16	1	16	1	21.25	23.50	13.50	0.50	5.50	14.31	FAB
18	1	16	1 ⅛	22.75	25.00	15.50	0.50	6.50	16.13	FAB
20	1	20	1 ⅛	25.00	27.50	17.25	0.50	7.25	18.00	FAB
24	1	20	1 ¼	29.50	32.00	19.50	0.50	7.50	21.56	FAB

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>