



Ball valve type 104 PVC-C 100-230V With solvent cement sockets Inch ASTM Inclusive 2 threaded valve ends NPT

Model:

- Voltage according data sheet
- Control range 90 °
- For easy installation and removal
- Integrated stainless steel mounting inserts

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	Voltage	EPDM Code	SP	Weight (kg)	FKM Code
16	10	3/8	10	70	100-230V	199 104 322	1	0.995	199 104 332
20	15	1/2	10	185	100-230V	199 104 323	1	0.995	199 104 333
25	20	3/4	10	350	100-230V	199 104 324	1	1.050	199 104 334
32	25	1	10	700	100-230V	199 104 325	1	1.120	199 104 335
40	32	1 1/4	10	1000	100-230V	199 104 326	1	1.290	199 104 336
50	40	1 1/2	10	1600	24-240V	199 104 347	1	2.010	199 104 357
63	50	2	10	3100	24-240V	199 104 348	1	2.395	199 104 358

H (mm)	L (mm)	Type of actuator	Inch (inch)	B (mm)
194	178.5	10Nm	3/8	50
194	178.5	10Nm	1/2	50
207	186.0	10Nm	3/4	58
217	192.5	10Nm	1	68
236	204.5	10Nm	1 1/4	84
275	208.5	20Nm	1 1/2	97
307	221.5	20Nm	2	124

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>