



## JRG Sanipex MT insulation box for ball valves EPP

- Description: half shells made of EPP for an easy, professional and economical insulation of JRG Sanipex MT ball valves with and without spindle extension
- Material: Expanded polypropylene (EPP)
- Temperature: max. 110°C
- Thermal conductivity: 0.035 W/mK according EN 12667
- Building material class: B2 according DIN 4102 and E according EN 13501-1

d (mm)	JRG Code	GF Code	PF	Weight (kg)	d1 (mm)	d2 (mm)	l (mm)
16	<b>6041.516</b>	<b>351 616 669</b>	2 J3 J77 110	0.010	53	58	96
20	<b>6041.520</b>	<b>351 620 669</b>	2 J3 J77 110	0.012	57	62	113
26	<b>6041.526</b>	<b>351 626 669</b>	2 J3 J77 110	0.012	63	68	133
32	<b>6041.532</b>	<b>351 632 669</b>	2 J3 J77 110	0.035	85	95	162
40	<b>6041.540</b>	<b>351 640 669</b>	2 J3 J77 110	0.065	104	122	189

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>