



ecoFIT Segmented Cross Tee Equal PE100 SDR17

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.5 as per ISO 4427-3**
- Pressure rating: 5 bar water

Note:

* Please call us for availability

	d	Code	Weight	z	z1	L	e
	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)
	90	P2314127090	1.10	450	225	180	5.4
	110	P2314127110	2.17	590	295	240	6.6
	125	P2314127125	2.80	605	303	240	7.4
	140	P2314127140	3.55	620	310	240	8.3
	160	P2314127160	4.72	640	320	240	9.5
	180	P2314127180	6.06	660	330	240	10.7
	200	P2314127200	7.60	680	340	240	11.9
	225	P2314127225	9.80	705	353	240	13.4
	250	P2314127250	14.78	850	425	300	14.8
	280	P2314127280	18.88	880	440	300	16.6
	315	P2314127315	31.11	1115	558	400	18.7
	355	P2314127355	40.25	1155	578	400	21.1
	400	P2314127400	51.92	1200	600	400	23.7
	450	P2314127450	67.17	1250	625	400	26.7
	500	P2314127500	93.18	1400	700	450	29.7
	630	P2314127630	181.72	1730	865	550	37.4
	710	P2314127710	236.00	1810	905	550	42.1
	800	P2314127800	372.08	2200	1100	700	47.4
	900	P2314127900	509.02	2400	1200	750	53.3
	1000	P2314127001	642.75	2500	1250	750	59.3
*	1200	P2314127002	922.10	2850	1350	750	71.1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>