



Type 2881-1K(D) to 2884-1K(D) PEEK Leitfähigkeitselektroden

Leit-/Widerstandsfähigkeit:

- $\pm 2\%$ Messgenauigkeit - Kunden-Kalibrationszertifikat beiliegend
- Zweifachgewinde
- Kompakte Elektrodenlänge für einfache In-Line-Installation
- Durchfluss-Design mit drei Öffnungen verringert Verstopfungen und Blaseneinschlüsse
- 316 SS Elektroden mit PEEK Prozessverbindungen
- Erfüllt die USP-Anforderungen

Schaft	Anschluss	Process Connection Size	Zell-Konstante (cm ⁻¹)	Operating Range	Kabellänge
Edelstahl	PEEK	3/4 inch MNPT	0.01	0.055 - 100 $\mu\text{S/cm}$	7.6 m (25 ft)
Edelstahl	PEEK	ISO 7/1 - R3/4	0.01	0.055 - 100 $\mu\text{S/cm}$	7.6 m (25 ft)
Edelstahl	PEEK	3/4 inch MNPT	0.10	1 - 1000 $\mu\text{S/cm}$	7.6 m (25 ft)
Edelstahl	PEEK	ISO 7/1 - R3/4	0.10	1 - 1000 $\mu\text{S/cm}$	7.6 m (25 ft)
Edelstahl	PEEK	3/4 inch MNPT	1.00	10 - 10000 $\mu\text{S/cm}$	7.6 m (25 ft)
Edelstahl	PEEK	ISO 7/1 - R3/4	1.00	10 - 10000 $\mu\text{S/cm}$	7.6 m (25 ft)

MFR	Code	NPK
3-2881-1K	159 002 144	
3-2881-1KD	159 002 150	
3-2882-1K	159 002 146	
3-2882-1KD	159 002 152	
3-2883-1K	159 002 148	
3-2883-1KD	159 002 154	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>