






## Butterfly valve type 567 PVC-U SF Hand lever with ratchet settings

### Model:

- Silicone free / paint-compatible
- Overall length according to EN 558, ISO 5752
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220

### Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on [www.gfps.com](http://www.gfps.com)



| d    | Size   | DN   | PN    | kv-value            | EPDM        | Weight | FKM         | Weight |
|------|--------|------|-------|---------------------|-------------|--------|-------------|--------|
| (mm) | (inch) | (mm) | (bar) | ( $\Delta p=1$ bar) | Code        | (kg)   | Code        | (kg)   |
|      |        |      |       | (l/min)             |             |        |             |        |
| 63   | 2      | 50   | 10    | 740                 | 161 567 402 | 1.040  | 161 567 422 | 1.044  |
| 75   | 2 ½    | 65   | 10    | 1500                | 161 567 403 | 1.350  | 161 567 423 | 1.148  |
| 90   | 3      | 80   | 10    | 2400                | 161 567 404 | 1.517  | 161 567 424 | 1.315  |
| 110  | 4      | 100  | 10    | 3800                | 161 567 405 | 2.528  | 161 567 425 | 1.983  |
| 140  | 5      | 125  | 10    | 8600                | 161 567 406 | 2.536  | 161 567 426 | 3.339  |
| 160  | 6      | 150  | 10    | 11400               | 161 567 407 | 3.541  | 161 567 427 | 3.564  |
| 225  | 8      | 200  | 10    | 19900               | 161 567 408 | 5.513  | 161 567 428 | 5.541  |

| d    | Hmax  | Lmax  | Wmax  | U    | V     | H4   | V1    | Lg   | D2   | Q1   | Q2   | Y    | M1    | M2    |
|------|-------|-------|-------|------|-------|------|-------|------|------|------|------|------|-------|-------|
| (mm) | (mm)  | (mm)  | (mm)  | (mm) | (mm)  | (mm) | (mm)  | (mm) | (mm) | (mm) | (mm) | (mm) | (mm)  | (mm)  |
| 63   | 278.9 | 115.2 | 269.0 | 90   | 133.3 | 23   | 78.8  | 45   | 104  | 40   |      | 66.8 | 64.7  | 205.5 |
| 75   | 291.8 | 115.2 | 271.8 | 90   | 139.9 | 23   | 85.1  | 46   | 115  | 54   | 35   | 66.8 | 64.7  | 205.5 |
| 90   | 303.6 | 115.2 | 273.9 | 90   | 145.6 | 23   | 91.2  | 49   | 131  | 67   | 50   | 66.8 | 64.7  | 205.5 |
| 110  | 342.2 | 115.2 | 336.0 | 90   | 166.4 | 23   | 105.7 | 56   | 161  | 88   | 74   | 70.1 | 64.9  | 255.5 |
| 140  | 368.9 | 115.2 | 349.0 | 90   | 180.0 | 23   | 118.8 | 64   | 187  | 113  | 97   | 70.1 | 64.9  | 255.5 |
| 160  | 390.0 | 115.2 | 363.0 | 90   | 189.0 | 23   | 130.9 | 72   | 215  | 139  | 123  | 70.1 | 64.9  | 255.5 |
| 225  | 455.1 | 149.4 | 543.0 | 90   | 210.5 | 23   | 158.3 | 73   | 267  | 178  | 169  | 86.3 | 103.6 | 409.5 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com) Internet: <http://www.gfps.com>