


membranaafsluiter type 514, PVC-U met lasmof, PE80

Uitvoering:

- materiaal: PVC-U/PE
- verdubbelde doorstroming
- één centrale kunststof schroefdraad vervangt 4 bouten
- vergrendelbaar handwiel
- radiaal in- en uitbouwbaar
- korte inbouw lengte

optioneel:

- individuele configuratie van de afsluiter mogelijk
- multifunctiemodule met geïntegreerde, zelfinstellende eindschakelaars
- voor PN16 configureerbaar



d (mm)	DN (mm)	Inch (inch)	PN (bar)	kv-waarde ($\Delta p=1$ bar) (L/min)	EPDM code	gewicht (kg)
20	15	½	10	125	161 514 212	0,290
25	20	¾	10	271	161 514 213	0,416
32	25	1	10	481	161 514 214	0,662
40	32	1 ¼	10	759	161 514 215	1,405
50	40	1 ½	10	1263	161 514 216	2,492
63	50	2	10	1728	161 514 217	3,331

d (mm)	D (mm)	D2 (mm)	D3 (mm)	L (mm)	L2 (mm)	H (mm)	H1 (mm)	H2 (mm)	M	z (mm)	indica- tor = Hx (mm)	inch bena- dering (inch)
20	65	65	43	128	25	73	14	12	M6	100	7	½
25	80	65	51	150	25	81	18	12	M6	118	10	¾
32	88	87	58	162	25	107	22	12	M6	126	13	1
40	101	87	72	184	45	115	26	15	M8	144	15	1 ¼
50	117	135	83	210	45	148	32	15	M8	164	19	1 ½
63	144	135	100	248	45	166	39	15	M8	194	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>