


Variable area flow meter short version type 123
Float in PVDF with magnet
With solvent cement sockets PVC-U metric
O-rings in EPDM

Model:

- Suitable limit switches see accessories for variable area flow meters
- Union nuts and valve ends in other materials on request

d (mm)	DN (mm)	Size (inch)	Scale range (l/h)	Type	Polysulfone Code	Weight (kg)	PVC-U transp. Code	Weight (kg)
16	10	3/8	2.5 - 25.0	SK 500	198 801 890	0.079	198 803 320	0.081
16	10	3/8	5.0 - 50.0	SK 510	198 801 891	0.102	198 803 321	0.080
16	10	3/8	10.0 - 100.0	SK 520	198 801 892	0.075	198 803 322	0.079
20	15	1/2	8.0 - 80.0	SK 600	198 801 893	0.123	198 803 323	0.129
20	15	1/2	15.0 - 150.0	SK 610	198 801 894	0.121	198 803 324	0.160
20	15	1/2	20.0 - 200.0	SK 620	198 801 895	0.119	198 803 325	0.125
32	25	1	15.0 - 150.0	SK 700	198 801 896	0.248	198 803 326	0.301
32	25	1	30.0 - 300.0	SK 710	198 801 897	0.289	198 803 327	0.255
32	25	1	50.0 - 500.0	SK 720	198 801 898	0.241	198 803 328	0.248
32	25	1	100.0 - 1000.0	SK 730	198 801 899	0.280	198 803 329	0.242

D (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)
35	199	171	165	3/4
35	199	171	165	3/4
35	199	171	165	3/4
43	223	191	185	1
43	223	191	185	1
43	223	191	185	1
60	250	206	200	1 1/2
60	250	206	200	1 1/2
60	250	206	200	1 1/2
60	250	206	200	1 1/2



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 3/28/26



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>