



Wafer-style intermediate installation butterfly valve type 145 PVC-U
With electric actuator 230V
Without manual override
Flange standard metric/ANSI/BS/JIS

Model:




- Voltage 100-230V, 50-60Hz
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Overall length according to EN 558, ISO 5752 (DN50-200 line 25, DN250-300 line 16)
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220

Option:

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit, Monitoring board, Position controller, Profibus DP board

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d	Size	DN	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(inch)	(mm)	(bar)	(Δp=1 bar)	Code	(kg)	Code	(kg)
				(l/min)				
63	2	50	10	740	199 145 042	4.408	199 145 062	4.182
75	2 ½	65	10	1500	199 145 043	4.509	199 145 063	4.286
90	3	80	10	2400	199 145 044	4.675	199 145 064	4.453
110	4	100	10	3800	199 145 045	6.890	199 145 065	5.073
140	5	125	10	8600	199 145 046	5.626	199 145 066	5.644
160	6	150	10	11400	199 145 047	6.631	199 145 067	6.654
225	8	200	10	19900	199 145 048	12.606	199 145 068	12.634
280	10	250	6	34000	199 145 049	14.334	199 145 069	14.481
315	12	300	4	50000	199 145 050	19.546	199 145 070	19.546

d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	Y	E	Y1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	393.3	190	118.4	90	133.3	23	78.8	45	104	40		166.2	122.3	15
75	406.2	190	132.5	90	139.9	23	85.1	46	115	54	35	166.2	122.3	15
90	426.1	190	136.8	90	145.6	23	91.2	49	131	67	50	189.3	122.3	
110	461.4	190	161.0	90	166.4	23	105.7	56	161	88	74	189.3	122.3	
140	488.1	190	187.0	90	180.0	23	118.8	64	187	113	97	189.3	122.3	
160	509.2	190	215.0	90	189.0	23	130.9	72	215	139	123	189.3	122.3	
225	568.1	190	267.0	90	210.5	23	158.3	73	267	178	169	199.3	122.3	
280	685.0	190	329.0	125	262.6	23	206.1	113	329	210	207	199.3	122.3	17
315	729.4	190	380.4	125	284.3	23	228.8	113	379	256	253	199.3	122.3	17

d	M1	M2
(mm)	(mm)	(mm)
63	107.3	82.7
75	107.3	82.7
90	107.3	82.7
110	107.3	82.7
140	107.3	82.7
160	107.3	82.7
225	107.3	82.7
280	107.3	82.7
315	107.3	82.7

Data sheet

valid from: 4/3/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>