



ecoFIT Segmented Bend 1.5D 60° PE100 SDR11

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 12.8 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e	
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	
90	P2316606090	0.96	228	150	135.0	8.2	
110	P2316606110	1.53	245	150	165.0	10.0	
125	P2316606125	2.08	259	150	187.5	11.4	
140	P2316606140	2.72	271	150	210.0	12.7	
160	P2316606160	3.78	289	150	240.0	16.6	
180	P2316606180	6.77	406	250	270.0	16.4	
200	P2316606200	8.70	423	250	300.0	18.2	
225	P2316606225	11.56	445	250	337.5	20.5	
250	P2316606250	14.86	467	250	375.0	22.7	
280	P2316606280	19.61	492	250	420.0	25.4	
315	P2316606315	28.95	573	300	472.5	28.6	
355	P2316606355	45.53	708	400	532.5	32.2	
400	P2316606400	60.76	746	400	600.0	36.3	
450	P2316606450	81.26	790	400	675.0	40.9	
500	P2316606500	105.53	833	400	750.0	45.4	
560	P2316606560	140.11	885	400	840.0	50.8	
630	P2316606630	189.33	946	400	945.0	57.2	
710	P2316606710	310.56	1215	600	1065.0	64.5	
*	800	P2316606800	418.11	1293	600	1200.0	72.6
*	900	P2316606900	563.68	1379	600	1350.0	81.7
*	1000	P2316606001	778.21	1466	600	1500.0	90.2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>