



Joelho 45° S5/SDR11 (PxP)

Model:

- Material: PP-H
- Solda de topo convercional conforme DVS 2207
- IR = Infrared welding compatible
- Versão longa para d250, d280 e d315

1) Material:PP-R

d	SDR	PN	FM	code	weight	L	L1	e
(mm)		(bar)			(kg)	(mm)	(mm)	(mm)
20	11	10	IR	727 158 506	0,006	32	24,0	1,9
25	11	10	IR	727 158 507	0,010	34	25,0	2,3
32	11	10	IR	727 158 508	0,021	36	25,0	2,9
40	11	10	IR	727 158 509	0,033	39	25,0	3,7
50	11	10	IR	727 158 510	0,054	42	26,0	4,6
63	11	10	IR	727 158 511	0,097	47	29,0	5,8
75	11	10	IR	727 158 512	0,137	49	29,0	6,8
90	11	10	IR	727 158 513	0,222	57	34,0	8,2
110	11	10	IR	727 158 514	0,412	70	43,0	10,0
125	11	10	IR	727 158 515	0,570	79	48,0	11,4
140	11	10	IR	727 158 516	0,854	88	55,0	12,7
160	11	10	IR	727 158 517	1,256	100	60,0	14,6
200	11	10	IR	727 158 519	2,448	124	75,0	18,2
225	11	10	IR	727 158 520	3,495	140	85,0	20,5
1	250	11	IR	727 158 521	7,890	225	133,0	22,7
1	280	11	IR	727 158 522	10,170	235	143,0	25,4
1	315	11	IR	727 158 523	11,690	255	154,0	28,6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>