




Robinet à bille type 546 Pro ABS sans silicone
Avec emboîture pour collage métrique

Exécution:


- Joint de bille: PVDF
- Inserts de fixation en acier inoxydable intégrés
- Cote z, extrémités de la vanne et écrous compatibles avec les types 546 (1ère génération)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Peut être équipé d'un servomécanisme pneumatique ou électrique de Georg Fischer
- Configuration individuelle de la vanne possible



d	DN	Pouces	PN	Valeur-kv	EPDM	CAN	SP	Poids
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code			(kg)
				(l/min)				
16	10	3/8	10	70	169 546 601		1	0.112
20	15	1/2	10	185	169 546 602		1	0.114
25	20	3/4	10	350	169 546 603		1	0.178
32	25	1	10	700	169 546 604		1	0.258
40	32	1 1/4	10	1000	169 546 605		1	0.457
50	40	1 1/2	10	1600	169 546 606		1	0.642
63	50	2	10	3100	169 546 607		1	1.175
75	65	2 1/2	10	5000	169 546 608		1	3.900
90	80	3	10	7000	169 546 609		1	5.700
110	100	4	10	11000	169 546 610		1	9.100



d	B3	DE1	G	H	H1	H4	L	Lz	M	M1	M2	z
(mm)	(mm)	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	25	50	M6	197	27	12	92	28	82	35	47	64
20	25	50	M6	197	27	12	95	28	82	35	47	64
25	25	58	M6	201	30	12	110	33	106	44	62	72
32	25	68	M8	207	36	12	123	36	106	44	62	79
40	45	84	M8	213	44	15	146	43	131	57	74	94
50	45	97	M8	219	51	15	157	45	131	57	74	95
63	45	124	M8	234	64	15	183	51	152	66	86	107
75	70	166	M8	234	85	15	233	68	270	64	206	144
90	70	200	M8	234	105	15	254	71	270	64	206	151
110	120	238	M12	234	123	22	301	82	320	64	206	174

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>