

Joint profilé EPDM/FKM Métrique

Exécution:

- Pour tous les collets GF métriques
- Dureté: 70° Shore **EPDM**, 75° Shore **FKM**
- **EPDM**: Approuvé selon DVGW eau W 270, recommandation KTW
- Centrage sur le diamètre intérieur de la vis
- Matériau âme en acier; St37
- Joint en caoutchouc-acier combiné avec un bourrelet en caoutchouc jusqu'à d630
- Joint en caoutchouc-acier idéal pour les grandes dimensions (d710 - d1000)


Le "di collets" indique le diamètre intérieur possible des collets

d (mm)	DN (mm)	PN (bar)	EPDM Code	CAN	FKM Code	CAN	Poids (kg)
16	10	16	748 440 705		749 440 705		0.012
20	15	16	748 440 706		749 440 706		0.013
25	20	16	748 440 707		749 440 707		0.014
32	25	16	748 440 708		749 440 708		0.019
40	32	16	748 440 709		749 440 709		0.026
50	40	16	748 440 710	474 817	749 440 710		0.039
63	50	16	748 440 711	474 818	749 440 711		0.050
75	65	16	748 440 712		749 440 712		0.082
90	80	16	748 440 713	474 821	749 440 713		0.083
110	100	16	748 440 714	474 822	749 440 714		0.127
125	100	16	748 440 715	474 822	749 440 715		0.105
140	125	16	748 440 716	474 823	749 440 716		0.173
160 - 180	150	16	748 440 717	474 824	749 440 717		0.207
200	200	16	748 440 719	474 865	749 440 719		0.263
225	200	16	748 440 720	474 865	749 440 720		0.255
250	250	16	748 440 721	474 866	749 440 721		0.462
280	250	16	748 440 722	474 866	749 440 722		0.323
315	300	16	748 440 723	474 867	749 440 723		0.549
355	350	16	748 440 724		749 440 724		0.870
400	400	16	748 440 725	474 868	749 440 725		1.088
450	500	10	748 440 726		749 440 726		0.718
500	500	10	748 440 727		749 440 727		0.718
560	600	10	748 440 728		749 440 728		0.923
630	600	10	748 440 729		749 440 729		0.923
710	700	6	748 440 730				0.890
800	800	6	748 440 731				1.340
900	900	6	748 440 732				1.170
1000	1000	6	748 440 733				1.360

d (mm)	D (mm)	D1 (mm)	di collets (mm)	H (mm)	H1 (mm)
16	46	16	6 - 16	4	3
20	51	20	10 - 20	4	3
25	61	22	12 - 22	4	3
32	71	28	18 - 28	4	3
40	82	40	30 - 40	4	3
50	92	46	36 - 46	4	3
63	107	58	48 - 58	5	4
75	127	69	59 - 69	5	4
90	142	84	73 - 84	5	4
110	162	104	94 - 104	6	5
125	162	123	113 - 123	6	5
140	192	137	127 - 137	6	5
160 - 180	218	160	150 - 160	8	6
200	273	203	192 - 203	8	6
225	273	220	207 - 220	8	6
250	328	252	238 - 252	8	6

Data sheet

valid from: 27/09/2024



d	D	D1	di collets	H	H1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
280	328	274	264 - 274	8	6
315	378	306	296 - 306	8	6
355	438	355	340 - 355	10	7
400	489	400	385 - 400	10	7
450	594	403	393 - 403	10	7
500	594	447	437 - 447	10	7
560	695	494	484 - 494	10	7
630	695	555	545 - 555	10	7
710	810	712	562 - 712	6	3
800	917	813	663 - 813	6	3
900	1017	915	765 - 915	6	3
1000	1124	1016	866 - 1016	6	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>