



Adaptor bush equal PVC-U metric / BS R

Model:

- With solvent cement socket metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

	d	d	Thread Type	Size	PN	Code	SP	Weight	z	L	s
	(mm)	(inch)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
*	16	3/8	R	3/8	16	721 910 705	10	0.011	20	34	27
*	20	1/2	R	1/2	16	721 910 706	10	0.018	24	40	32
*	25	3/4	R	3/4	16	721 910 707	10	0.025	25	44	36
*	32	1	R	1	16	721 910 708	10	0.039	28	50	46
*	40	1 1/4	R	1 1/4	16	721 910 709	10	0.061	31	57	55
*	50	1 1/2	R	1 1/2	16	721 910 710	10	0.092	32	63	65
*	63	2	R	2	16	721 910 711	5	0.161	38	76	80
*	75	2 1/2	R	2 1/2	10	721 910 712	6	0.227	42	86	90
	90	3	R	3	10	721 910 713	5	0.389	46	97	110
	110	4	R	4	10	721 910 714	5	0.572	53	114	130
		3/8	R	3/8	15	721 911 705	10	0.013	20	34	27
		1/2	R	1/2	15	721 911 706	10	0.017	24	40	32
		3/4	R	3/4	15	721 911 707	10	0.022	25	44	36
		1	R	1	15	721 911 708	10	0.037	28	50	46
		1 1/4	R	1 1/4	15	721 911 709	10	0.055	31	57	55
		1 1/2	R		15	721 911 710	10	0.097	32	63	65
		2	R	2	15	721 911 711	5	0.176	38	76	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>