





Spigot saddle with cutter

- 10 bar Gas / 16 bar Water
 - Complete with lower part
 - 4mm pin connectors
 - Limited path fusion indicators
 - d355-400mm. Not suitable for pipes if wall thickness is larger than SDR17 pipes.
- * Topload: delivery without lower part for assembling as Topload with tool no. 799.350.477; angleadaptor (799.350.340) for fusion cable required



d	d2	DN	PN	Code	Weight	Db	W	H	H1	SLW	SDR pipe
(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	
63	32	50	16	193 131 234	0.469	19	164	145	50	13	9 - 11
63	63	50	16	193 131 237	1.036	32	164	152	50	17	9 - 11
75	32	65	16	193 131 244	0.618	19	164	151	50	13	9 - 11
75	63	65	16	193 131 247	1.166	32	164	158	50	17	9 - 11
90	32	80	16	193 131 254	0.543	19	164	158	50	13	9 - 11
90	63	80	16	193 131 257	1.128	32	164	165	50	17	9 - 11
110	32	100	16	193 131 264	0.607	19	164	168	50	13	9 - 17.6
110	63	100	16	193 131 267	1.195	32	164	175	50	17	9 - 17.6
125	32	100	16	193 131 274	0.659	19	164	176	50	13	11 - 17.6
125	63	100	16	193 131 277	1.224	32	164	183	50	17	9 - 17.6
140	32	125	16	193 131 284	0.679	19	164	183	50	13	11 - 17.6
140	63	125	16	193 131 287	1.224	32	164	190	50	17	9 - 17.6
160	32	150	16	193 131 294	0.652	19	164	193	50	13	11 - 17.6
160	63	150	16	193 131 297	0.850	32	164	200	50	17	9 - 17.6
180	32	150	16	193 131 304	0.777	19	164	203	50	13	17 - 26
180	63	150	16	193 131 307	1.316	32	164	210	50	17	9 - 26
200	32	200	16	193 131 314	0.854	19	164	213	50	13	17 - 26
200	63	200	16	193 131 317	1.352	32	164	220	50	17	11 - 26
225	32	200	16	193 131 324	0.856	19	164	226	50	13	17 - 26
225	63	200	16	193 131 327	1.324	32	164	233	50	17	21 - 26
250	32	250	16	193 131 334	0.787	19	164	238	50	13	11 - 26
250	63	250	16	193 131 337	1.348	32	164	245	50	17	17 - 26
280	63	250	16	193 131 348	0.830	35	164	260	50	17	17 - 26
315	63	300	16	193 131 358	1.094	35	164	298	50	17	17 - 33
*	355	63	350	193 131 357	1.094	35	165	298	50	17	21 - 33
*	400	63	400	193 131 377	0.830	35	165	320	50	17	21 - 33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>