



Type 2350 Temperature Sensor

Temperature/Pressure:

- Wetted Materials: PDVF
- Additional features: Platinum RTD in extended tip for quick response
- In-line Mounting styles: 3/4 inch NPT
- Submersible mounting: 3/4 inch NPT
- Operating Temperature:\*\* In-line: -10° to 100°C (14 to 212°F) Submersible: -10° to 85°C (14° to 185°F)
- Operating Pressures:\*\* 0 to 16 bar (0 to 232 psi)
- Compatibility: 8900, 9900 or 9950
- \*\*check operating temperature/pressure graphs in catalog for derating information

Process Con- nection	Process Con- nection Size	MFR #	Communica- tion Interface	Electrical connction	Cable length (m)
Thread	19 mm NPT	3-2350-1	S <sup>3</sup> L		
Thread	19 mm NPT	3-2350-3	4-20 mA		

Operating Range	Cable Length	Code
	4.6m (15 ft.)	159 000 021
	4.6m (15 ft.)	159 000 920

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>