




PVC-U Ball Valve type 546 Pro
Silicone free
With backing flanges PVC-U ANSI

Model:


- Lockable lever as standard
- Ball seat PVDF
- Integrated stainless steel mounting inserts
- z-dimension, valve end and union nut are compatible with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of valves possible



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
70	65	2 1/2	16	5000	161 546 188	1	7.300	161 546 198	1	7.300
90	80	3	16	7000	161 546 189	1	10.600	161 546 199	1	10.600
110	100	4	16	11000	161 546 190	1	16.400	161 546 200	1	16.400



d (mm)	b1 (mm)	B3 (mm)	D1 (mm)	DE1 (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	k1 (mm)	L (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)
70	18	70	166	166	M8	169	85	15	140	290	68	270	64	205
90	20	70	200	200	M8	180	105	15	152	310	71	270	64	205
110	20	120	238	238	M12	194	123	22	190	350	82	326	71	205

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>