





546Pro 球阀 PVC-U#无硅
带PVC-U活套法兰端#美标

型号:

- Lockable lever as standard
- PVDF球密封
- 内置不锈钢固定螺孔
- Z尺寸、阀端和活接螺母与546型球阀（第1代）兼容

选项:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- 可配GF气动或电动执行器
- 可提供其他阀门配置



d	DN	Size	PN	kv-value	EPDM	SP weight	FKM	SP weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	code	(kg)	code	(kg)
				(l/min)				
70	65	2 1/2	16	5000	161 546 188	1 7,300	161 546 198	1 7,300
90	80	3	16	7000	161 546 189	1 10,600	161 546 199	1 10,600
110	100	4	16	11000	161 546 190	1 16,400	161 546 200	1 16,400

d	b1	B3	D1	DE1	G	H	H1	H4	k1	L	Lz	M	M1	M2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
70	18	70	166	166	M8	169	85	15	140	290	68	270	64	205
90	20	70	200	200	M8	180	105	15	152	310	71	270	64	205
110	20	120	238	238	M12	194	123	22	190	350	82	326	71	205

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com