




COOL-FIT 4.0 Coupler d32-d225

Model:

- Pre-insulated PE100 SDR 11 metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- Electrofusion fitting with integrated sealing lip, for a moisture-proof and vapour tight sealing



d	D	DN	SDR	PN	Code	Weight	D1	L	L1	z
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)	(mm)
32	90	25	11	16	738 913 108	0.179	97	127	36	5
40	110	32	11	16	738 913 109	0.129	117	133	40	3
50	110	40	11	16	738 913 110	0.169	117	141	44	3
63	125	50	11	16	738 913 111	0.240	132	149	48	3
75	140	65	11	16	738 913 112	0.520	147	163	55	3
90	160	80	11	16	738 913 113	0.750	168	178	62	4
110	180	100	11	16	738 913 114	0.831	188	198	72	4
140	225	125	11	16	738 913 116	1.565	233	221	84	3
160	250	150	11	16	738 913 117	1.726	258	233	90	3
225	315	200	11	16	738 913 120	3.783	324	275	110	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>