






PROGEF Standard Ball Valve type 546 Pro
With fusion sockets PE100 ISO

Model:

- Lockable lever as standard
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- z-dimension, valve end and union nut are compatible with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of valves possible



d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
				(l/min)						
16	10	3/8	10	71	167 546 161	1	0.120	167 546 171	1	0.120
20	15	1/2	10	185	167 546 162	1	0.120	167 546 172	1	0.120
25	20	3/4	10	350	167 546 163	1	0.180	167 546 173	1	0.180
32	25	1	10	700	167 546 164	1	0.258	167 546 174	1	0.260
40	32	1 1/4	10	1000	167 546 165	1	0.450	167 546 175	1	0.450
50	40	1 1/2	10	1600	167 546 166	1	0.630	167 546 176	1	0.630
63	50	2	10	3100	167 546 167	1	1.113	167 546 177	1	1.195

d	B3	DE1	G	H	H1	H4	L	Lz	z	M	M1	M2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	25	50	M6	60.5	27	12	93	28	67	82	35	47
20	25	50	M6	60.5	27	12	95	28	66	82	35	47
25	25	58	M6	74.0	30	12	109	33	77	106	44	62
32	25	68	M8	80.0	36	12	119	36	83	106	44	62
40	45	84	M8	95.0	44	15	171	43	99	131	57	74
50	45	97	M8	101.5	51	15	147	45	105	131	57	74
63	45	124	M8	116.5	64	15	168	51	117	152	66	86

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>