



ecoFIT Segmented Bend 1.5D 45° PE100 SDR7.4

Model:

- Long spigot for butt- and electrofusion welding
- Production process: segment welded
- Application: Water distribution
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 20 bar water

d (mm)	Code	Weight (kg)	Z (mm)	L (mm)	R (mm)	e (mm)
90	P2318605090	1.37	232	150	198.0	12.3
110	P2318605110	2.60	291	200	220.0	15.1
125	P2318605125	3.42	293	200	225.0	17.1
140	P2318605140	4.29	293	200	224.0	19.2
160	P2318605160	5.68	299	200	240.0	21.9
180	P2318605180	7.42	312	200	270.0	24.6
200	P2318605200	9.60	324	200	300.0	27.4
225	P2318605225	12.74	340	200	337.5	30.8
250	P2318605250	18.78	405	250	375.0	34.2
280	P2318605280	24.44	424	250	420.0	38.3
315	P2318605315	39.77	546	350	472.5	43.1
355	P2318605355	52.92	571	350	532.5	48.5
400	P2318605400	70.72	599	350	600.0	54.7
450	P2318605450	94.15	630	350	675.0	61.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>