



**Type 2350 Temperature Sensor**

**Temperature/Pressure:**

- Wetted Materials: PDVF
- Additional features: Platinum RTD in extended tip for quick response
- In-line Mounting styles: 3/4 inch NPT
- Submersible mounting: 3/4 inch NPT
- Operating Temperature:\*\* In-line: -10° to 100°C (14 to 212°F) Submersible: -10° to 85°C (14° to 185°F)
- Operating Pressures:\*\* 0 to 16 bar (0 to 232 psi)
- Compatibility: 8350, 8900 or 9900
- \*\*check operating temperature/pressure graphs in catalog for derating information

MFR #	Communica- tion Interface	Cable Length	Code
3-2350-1	Digital (S <sup>3</sup> L)	4.6m (15 ft.)	<b>159 000 021</b>
3-2350-3	4-20 mA	4.6m (15 ft.)	<b>159 000 920</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>