


## 2610 Process Optical Dissolved Oxygen Sensor



### Dissolved Oxygen:

- One year measurement cap life
- Optical DO measurement no flow requirements
- Rugged construction
- Calibration built into the measurement cap 2% of range 0 to 20 mg/l
- No membranes or filling solutions
- Flexible communications, 4 to 20 mA or Modbus (RS485)
- Measurement Range: 0 to 20 mg/L



MFR #	Description	Code
3-2610-51	Gen II Optical Dissolved Oxygen Sensor (0 to 20 ppm) with Digital S3L, 4 to 20 mA, and Modbus output	159 001 849
3-2610.392	Replacement Optical Dissolved Oxygen Sensor Cap (0 to 20 ppm)	159 310 122
3-2610.394	Replacement Optical Dissolved Oxygen Sensor cap (0 to 20 ppm) for Gen II 3-2610-51 DO Sensor	159 310 301
3-2610.501	Dissolved Oxygen Threaded Pipe Adapter	159 500 413

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>