




PROGEF Standard Metering ball valve type 523 Pro
With butt fusion spigots IR-Plus SDR11 metric

Model:


- Material: PP-H
- Micro-doser
- Excellent control characteristics
- Designed for easy installation and removal
- Ball seat PTFE
- Angle of operation 180° with scale
- Integrated stainless steel mounting inserts
- Z-length, end connectors and union nuts compatible to Type 523

Option:


- Other materials on demand



d	DN	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code	(kg)
			(l/min)				
20	15	10	20	167 523 482	0.130	167 523 492	0.130



d	M1	M2	Lz1	Lz2	L	V1	H	Hmax	DE	BG	B3	H4	U	s
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(mm)	(mm)
20	35	47	28	28	130	27	72	99	50	M6	25	12	59	1.9



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>