



ecoFIT Segmented Bend 1.5D 60° PE100 SDR9

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 16 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e	
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	
90	P2317606090	1.27	254	150	180.0	10.1	
110	P2317606110	2.23	302	200	176.0	12.3	
125	P2317606125	2.98	308	200	187.5	14.0	
140	P2317606140	3.86	321	200	210.0	15.7	
160	P2317606160	5.27	339	200	240.0	17.9	
180	P2317606180	7.08	356	200	270.0	20.1	
200	P2317606200	9.14	373	200	300.0	22.4	
225	P2317606225	12.17	395	200	337.5	25.2	
250	P2317606250	17.77	467	250	375.0	27.9	
280	P2317606280	23.57	493	250	420.0	31.3	
315	P2317606315	37.66	623	350	472.5	35.2	
355	P2317606355	50.51	657	350	532.5	39.7	
400	P2317606400	67.74	696	350	600.0	44.7	
450	P2317606450	90.75	740	350	675.0	50.3	
*	500	P2317606500	126.19	833	400	750.0	55.8
*	560	P2317606560	168.08	885	400	840.0	62.5
*	630	P2317606630	238.98	996	450	945.0	70.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>